



The Impact range of portable multi-gas monitors is able to monitor and display up to four gases simultaneously

Impact Personal multi-gas monitors



Reliable Operation

- Pre-calibrated plug-in sensor cartridge
- High specification sensors
- Patented Surecell™ toxic sensors
- Stable and accurate

Easy to Use

- One button on/off
- Multi-lingual, intuitive menu system
- On screen prompts guide user
- Built-in correction factors for flammable gases
- Minimal training required

Easy to Maintain

- Plug-in operation for all serviceable parts
- Cartridge replacement in less than one minute
- Re-calibration in less than two minutes when using Enforcer
- Minimised cost of ownership

Durable Housing

- Waterproof to IP67
- Rugged and impact resistant
- Built for everyday use

Alarm Indication

- 3 levels of instantaneous alarm, time weighted average alarms on toxic
- Periodic confidence flash and bleep
- Increasingly rapid flashing, ultra-bright alarm LEDs
- Powerful two tone audible alarm
- Vibrating alarm for noisy environments*
- Safelink communications*

User Friendly Pre-entry Check

- Peak hold function and drop line
- Hand aspiration
- Built-in automatic pump*
- Totally flexible

*Impact Pro model only

The Impact range of portable multi-gas monitors is able to monitor and display up to four gases simultaneously.

Using high specification flammable, oxygen and patented Surecell™ toxic sensors, our unique cartridge technology ensures safe, accurate and reliable measurements are always made. Impact and Impact Pro have MED approval.

Available in two configurations, the Impact and Impact Pro accepts either disposable and/or serviceable cartridges respectively, all of which are pre-calibrated and can be replaced in under one minute, so simplifying maintenance and minimising cost wherever possible. Compact and rugged these monitors are designed for tough working environments while being small, lightweight and unobtrusive, making them ideal for use in confined spaces where entry and exit may be difficult.

Designed to work how you want to; gas checks prior to entering a confined space can be carried out using a drop line, hand aspirator or via an optional built-in pump (supplied as standard on the Impact Pro) that turns on and off automatically when the sampling tube is connected.

Ultra-bright alarm lights and a powerful audible alarm, coupled with a periodic green flash and bleep provide user confidence that monitoring is always in operation and alarms are never missed. For noisy environments a vibrating alarm is included as standard on the Impact Pro. A large, multi-lingual, backlit display, with intuitive menu system simplifies use and minimises operator training.

Available for use with a wide range of accessories including the unique Enforcer calibration system and compliance friendly Safelink communication system, you can be sure that the Impact range of portable multigas monitors will be ready to protect you when most needed.



General Specification



General Specification

Use	Portable multigas monitor for the protection of personnel from up to four hazardous gases in the working environment.																
Available to detect[#]	Flammable, Oxygen, Carbon Monoxide, Hydrogen Sulfide, Sulfur Dioxide, Chlorine, Nitrogen Dioxide, Ammonia, Carbon Dioxide.																
User interface	Ultra clear, backlit, alphanumeric display. Intuitive push button menu system with user selectable operation in English, French, German, Italian, Spanish and Dutch. Other languages available upon request.																
Configuration and data download	Supplied configured, ready to use including data-logging as standard. Configurable via optional PC software and base station for control of logging functions and data download.																
Construction	Impact resistant plastic, anti-static to EN50014.																
Dimensions	49mm x 84mm x 136mm (1.9" x 3.3" x 5.3")																
Weight	Maximum 520g (18oz) including rechargeable battery and optional pump.																
IP rating	Instrument IP67 (NEMA 4 & 6).																
Operating temperature[#]	-20°C to +55°C (-4°F to +131°F).																
Storage temperature[#]	Instrument -40°C to +80°C (-40°F to +176°F).																
Humidity range[#]	Continuous 20 to 90%RH. Intermittent 0-99%RH non-condensing.																
Alarms	3 levels of instantaneous alarm per channel. Time weighted average alarms on toxic channels. Supplied pre-set (user configurable via optional PC software and base station).																
Audible alarm	Periodic confidence beep with differing dual tone for fault, gas alarm and warning rated 85dBA at 1m (90dBA at 1ft).																
Visual alarm	Green confidence flash with rapid red flashing for fault, gas alarm and warning indication.																
Battery performance	Ni-MH rechargeable, operating life > 10 hours (Charging time 7 hours). Dry cell disposable > 17 hours. Nominal reduction of 10% when used with pump.																
Optional pump	Supplied as standard with Impact Pro. Typical flow rate 0.3l/min. Automatic start/stop feature with auto-test on start-up and flow fail alarm.																
Approvals	<table border="0"> <tr> <td>Europe:</td> <td>II 2 G Ex ia d IIC (ATEX).</td> </tr> <tr> <td>USA:</td> <td>Class 1, Div 1, Groups A, B, C, D (UL).</td> </tr> <tr> <td>Canada:</td> <td>Class 1, Div 1, Groups A, B, C, D (CSA).</td> </tr> <tr> <td>Australia (surface):</td> <td>Ex ia s Zone 0, I/IB, T4.</td> </tr> <tr> <td>Australia (mines):</td> <td>MDA GD 5053.</td> </tr> <tr> <td>DMT:</td> <td>DMT O2 ATEX G 001 PFG Nr. 41300502.</td> </tr> <tr> <td>Brazil:</td> <td>BR-Ex ia d IIC T4 (INMETRO).</td> </tr> <tr> <td>Marine:</td> <td>Marine Equipment Directive MED 96/98/EC </td> </tr> </table>	Europe:	II 2 G Ex ia d IIC (ATEX).	USA:	Class 1, Div 1, Groups A, B, C, D (UL).	Canada:	Class 1, Div 1, Groups A, B, C, D (CSA).	Australia (surface):	Ex ia s Zone 0, I/IB, T4.	Australia (mines):	MDA GD 5053.	DMT:	DMT O2 ATEX G 001 PFG Nr. 41300502.	Brazil:	BR-Ex ia d IIC T4 (INMETRO).	Marine:	Marine Equipment Directive MED 96/98/EC
Europe:	II 2 G Ex ia d IIC (ATEX).																
USA:	Class 1, Div 1, Groups A, B, C, D (UL).																
Canada:	Class 1, Div 1, Groups A, B, C, D (CSA).																
Australia (surface):	Ex ia s Zone 0, I/IB, T4.																
Australia (mines):	MDA GD 5053.																
DMT:	DMT O2 ATEX G 001 PFG Nr. 41300502.																
Brazil:	BR-Ex ia d IIC T4 (INMETRO).																
Marine:	Marine Equipment Directive MED 96/98/EC																
Standard supply	Each instrument is supplied complete with quick start guide, multi-lingual operating instructions on CD, dry cell battery holders and batteries, belt clip and flow adaptor. Fully configured and ready to accept either disposable or serviceable sensor cartridges the key considerations in selecting either the Impact or Impact Pro are highlighted below.																

	Impact	Impact Pro
Cartridge type [#]	Disposable only	Disposable or Serviceable
Integral pump/pump adaptor	No	Yes
Vibrating alarm	No	Yes
Safelink	No	Yes

Ordering information

e.g. 2302B1000 **9 B E** = 2302B1000**9BE**

TYPE	CERTIFICATION	LANGUAGE
8 Impact	U USA Canada	U UL CSA CSA
9 Impact Pro	B Europe Australia Australia Mines Brazil	ATEX ATEX SAA SAA MDA MDA INMETRO INMETRO
		E English* F French G German I Italian S Spanish D Dutch *Default

Optional accessories

A wide range of optional accessories are available including:
 Base station and Impact Configuration Utility (required for data download and configuration).
 Rechargeable NiMH batteries for use with base station or offline charger.
 Enforcer calibration system.
 Safelink communication system.
 Pre-entry sample probes including hand aspirator, 1m probe, tubing and ball float.
 Body harness and harness clip offering alternate mounting arrangements.
 Field case for housing of all accessories as required.

[#] Refer to cartridge datasheet for gas specific data

Honeywell Analytics Gas Detection



Honeywell Analytics is able to provide gas detection solutions to meet the requirements of all applications and industries. Contact us in the following ways:

Headquarters

Europe, Middle East, Africa

Life Safety Distribution AG

Javastrasse 2

8604 Hegnau

Switzerland

Tel: +41 (0)44 943 4300

Fax: +41 (0)44 943 4398

gasdetection@honeywell.com

Customer Service:

Tel: 00800 333 222 44 (Freephone number)

Tel: +41 44 943 4380 (Alternative number)

Fax: 00800 333 222 55

Middle East Tel: +971 4 450 5800 (Fixed Gas Detection)

Middle East Tel: +971 4 450 5852 (Portable Gas Detection)

Americas

Honeywell Analytics Distribution Inc.

405 Barclay Blvd.

Lincolnshire, IL 60069

USA

Tel: +1 847 955 8200

Toll free: +1 800 538 0363

Fax: +1 847 955 8210

detectgas@honeywell.com

Asia Pacific

Honeywell Analytics

Asia Pacific

#701 Kolon Science Valley (1)

43 Digital-Ro 34-Gil, Guro-Gu

Seoul 152-729

Korea

Tel: +82 (0) 2 6909 0300

Fax: +82 (0) 2 2025 0388

India Tel: +91 124 4752700

analytics.ap@honeywell.com

Technical Support Centres

Honeywell Analytics Ltd.

4 Stinsford Road

Nuffield Industrial Estate

Poole, Dorset, BH17 0RZ

United Kingdom

Tel: +44 (0) 1202 645 544

Fax: +44 (0) 1202 645 555

Honeywell Analytics

ZAC Athélia 4 - 375 avenue du Mistral

Bât B, Espace Mistral

13600 La Ciotat

France

Tel: +33 (0) 4 42 98 17 75

Fax: +33 (0) 4 42 71 97 05

Honeywell Analytics

Elsenheimerstrasse 43

80687 München

Germany

Tel: +49 89 791 92 20

Fax: +49 89 791 92 43

Honeywell Analytics

P.O. Box-45595

6th Street

Musaffah Industrial Area

Abu Dhabi

UAE

Tel: +971 2 554 6672

Fax: +971 2 554 6672

EMEA: HAexpert@honeywell.com

US: ha.us.service@honeywell.com

AP: ha.ap.service@honeywell.com

www.honeywellanalytics.com

www.raesystems.com

Honeywell Analytics
Experts in Gas Detection

BWF
Technologies
by Honeywell

RAE
SYSTEMS
by Honeywell

Please Note:

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.

10722_H_Impact/Impact Pro_DS0280_V7_EMEA

05/13

© 2013 Honeywell Analytics

Honeywell